

Replacing ProOne® G2.0 Filters

When should I change my filters?

If you notice a difference in the taste/smell of your water and/or a slowdown in the flow rate, this may indicate your filters need to be cleaned. If after cleaning, the flow rate does not increase or you still notice the same taste/smell, it may be time for replacement.

<u>ProOne System:</u>	<u>Filter Options:</u>	<u>Replacement Time:</u>	<u>Cycle Time:</u>
Traveler +	(1) ProOne 5"	Up to (6) months	3.5 Hours
Big II	(1) ProOne 5"	Up to (6) months	4.5 Hours
	(2) ProOne 7"	Up to (12) months	3.5 Hours
Big +	(1) ProOne 7"	Up to (6) months	4 Hours
	(2) ProOne 9"	Up to (12) months	3 Hours
	(3) ProOne 9"	Over (18) months	1.5 Hours

How often should I clean my filters and system?

It's recommended you clean your entire system once a month.

Cleaning the Filters

It is important to not allow water to leak into the blue stem of the plastic base. Hold filters by the base and place under cool running water for about 2 minutes. While continuously running under water, scrub the white ceramic material with the abrasive side of included sponge. Rinse well and lay on side until ready to install. Do NOT use soap on the filter. Do NOT allow water to enter the stem of the filter.

Installing the Filters

1. Take (e) filter and place (e1) rubber washer onto stem.
2. Insert filter stem through hole(s) in (c) upper container.
3. Screw on (e2) wing nut on underside of (c) upper container. Follow steps (1.) and (2.) for each filter. Do NOT over tighten.
4. Plug any remaining hole with the (f) rubber stoppers included.
5. Place (c) upper container onto (d) lower container.

